

NAME

CURLOPT_MAIL_RCPT – provide list of mail recipients

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_MAIL_RCPT,  
                          struct curl_slist *rcpts);
```

DESCRIPTION

Pass a pointer to a linked list of recipients to pass to the server in your SMTP mail request. The linked list should be a fully valid list of **struct curl_slist** structs properly filled in. Use *curl_slist_append(3)* to create the list and *curl_slist_free_all(3)* to clean up an entire list.

When performing a mail transfer, each recipient should be specified within a pair of angled brackets (<>), however, should you not use an angled bracket as the first character libcurl will assume you provided a single email address and enclose that address within brackets for you.

When performing an address verification (VRFY command), each recipient should be specified as the user name or user name and domain (as per Section 3.5 of RFC5321).

When performing a mailing list expand (EXPN command), each recipient should be specified using the mailing list name, such as "Friends" or "London-Office".

DEFAULT

NULL

PROTOCOLS

SMTP

EXAMPLE

TODO

AVAILABILITY

Added in 7.20.0. The VRFY and EXPN logic was added in 7.34.0

RETURN VALUE

Returns CURLE_OK if the option is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_MAIL_FROM(3), CURLOPT_MAIL_AUTH(3),